



## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

Safety Data Sheet dated 16/10/2017, version 30

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: Cth30 Polyurethane Hardner 451

Trade code: 385348

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Surface coating

---

1.3. Details of the supplier of the safety data sheet

Company:

Sirca S.p.A.

Address:

Viale Roma, 85  
35010 S. Dono di Massanzago (PD) - ITALY  
Tel. +39 0499322311

Competent person responsible for the safety data sheet:

safety@sirca.it

1.4. Emergency telephone number

National Poisons Information Service - Medical Center Chaim Shiba - Tel Ha' shomer - Phone

+972 - 3 - 5303030

Sirca S.p.A. +39 049 9322311 (08.00 - 17.00) From Monday to Friday

#### SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards known

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

#### Precautionary statements:

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P370+P378 In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders to extinguish.

#### Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

#### Contains

n-butyl acetate

ethyl acetate

Alifatic-aromatic polyisocyanate

toluene

hexamethylene-di-isocyanate: May produce an allergic reaction.

#### Special provisions according to Annex XVII of REACH and subsequent amendments:

None

#### 2.3. Other hazards

This product contains isocyanates. Producer's specifications are as follows: ready-to-use paints containing isocyanates may irritate mucosae, particularly those of the respiratory system, and may give rise to hypersensitivity reactions. Vapour or aerosol inhalation may lead to sensitization. Please take all the measures used for all solvent-containing paints while manipulating isocyanate-containing paints. Avoid vapour and aerosol inhalation. People with allergic or asthmatic precedents or subject to respiratory disorders should not handle paints containing isocyanates.

#### Other Hazards:

No other hazards known

---

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 25% - < 48% n-butyl acetate

REACH No.: 01-2119485493-29-xxxx, Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 25% - < 48% ethyl acetate

REACH No.: 01-2119475103-46-xxxx, Index number: 607-022-00-5, CAS: 141-78-6, EC:

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

205-500-4

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 20% - < 25% Alifatic-aromatic polyisocyanate

CAS: 26426-91-5

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.4.2/1 Skin Sens. 1 H317

>= 7% - < 9.9% toluene

REACH No.: 01-2119471310-51-xxxx, Index number: 601-021-00-3, CAS: 108-88-3, EC: 203-625-9

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.7/2 Repr. 2 H361

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.8/3 STOT SE 3 H336

>= 5% - < 7% butanone

REACH No.: 01-2119457290-43-xxxx, Index number: 606-002-00-3, CAS: 78-93-3, EC: 201-159-0

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 0.1% - < 0.2% hexamethylene-di-isocyanate

REACH No.: 01-2119457571-37-xxxx, Index number: 615-011-00-1, CAS: 822-06-0, EC: 212-485-8

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.1/1/Inhal Acute Tox. 1 H330

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.4.1/1 Resp. Sens. 1 H334

⚠ 3.4.2/1 Skin Sens. 1 H317

---

## SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Induce vomiting only on doctor's advice

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

Contact a poisons centre

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

---

#### SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Combustion may liberate toxic or very toxic gases. Do not breathe fumes.

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Eliminate all unguarded flames and possible sources of ignition. Do not smoke.

6.3. Methods and material for containment and cleaning up

Collect the spilled product with no-sparking tools.

Rapidly recover the product. To do so, wear a mask and protective clothing.

Recover the product for re-use if possible, or for elimination. The product might, where appropriate, be absorbed by inert material.

After the product has been recovered, rinse the area and materials involved with water.

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

- 6.4. Reference to other sections  
See also section 8 and 13

---

#### SECTION 7: Handling and storage

- 7.1. Precautions for safe handling  
Keep away from flame and sparks. Avoid accumulating electrostatic charge.  
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.  
Avoid contact with skin and eyes, inhalation of vapours and mists.  
Exercise the greatest care when handling or opening the container.  
Don't use empty container before they have been cleaned.  
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.  
Contaminated clothing should be changed before entering eating areas.  
Do not eat or drink while working.  
Do not smoke while working.  
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities  
Store at below 30 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.  
Keep away from food, drink and feed.  
Incompatible materials:  
None in particular.  
Instructions as regards storage premises:  
Cool and adequately ventilated.  
Safety electric system.
- 7.3. Specific end use(s)  
No further recommendations. Refer to point 1.2

---

#### SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters  
n-butyl acetate - CAS: 123-86-4  
TWA (Italia) - TWA: 150 ppm - STEL: 200 ppm  
ACGIH - TWA: 150 ppm - STEL: 200 ppm - Notes: Eye and URT irr
- ethyl acetate - CAS: 141-78-6  
(OEL (IT)) - TWA: 400 ppm  
ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr
- toluene - CAS: 108-88-3  
(OEL (IT)) - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - Behaviour: Binding - Notes: Pelle  
EU - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Skin  
ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss
- butanone - CAS: 78-93-3  
(OEL (IT)) - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm - Behaviour:  
Binding  
EU - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm  
ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS  
impair
- hexamethylene-di-isocyanate - CAS: 822-06-0  
(OEL (IT)) - TWA: 0.005 ppm  
ACGIH - TWA(8h): 0.005 ppm - Notes: URT irr, resp sens
- DNEL Exposure Limit Values

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

n-butyl acetate - CAS: 123-86-4

Worker Professional: 600 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Professional: 300 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 300 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 35.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

ethyl acetate - CAS: 141-78-6

Worker Industry: 1468 mg/m<sup>3</sup> - Consumer: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 1468 ppm - Exposure: Human Inhalation - Frequency: Short Term (acute)

Worker Industry: 63 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 4.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)

Consumer: 734 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 37 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, local effects

Consumer: 367 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 367 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

toluene - CAS: 108-88-3

Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 226 mg/m<sup>3</sup> - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 56.5 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 8.13 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Industry: 384 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term,

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

systemic effects  
 Worker Industry: 384 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 192 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

butanone - CAS: 78-93-3  
 Worker Industry: 1161 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 600 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 412 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Consumer: 106 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 31 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

hexamethylene-di-isocyanate - CAS: 822-06-0  
 Worker Industry: 0.07 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 0.035 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 0.035 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4  
 Target: Fresh Water - Value: 0.18 mg/l  
 Target: Marine water - Value: 0.018 mg/l  
 Target: Freshwater sediments - Value: 0.981 mg/kg  
 Target: Marine water sediments - Value: 0.0981 mg/kg  
 Target: Soil (agricultural) - Value: 0.0903 mg/kg  
 Target: STP - Value: 35.6 mg/l

ethyl acetate - CAS: 141-78-6  
 Target: Fresh Water - Value: 0.26 mg/l  
 Target: Marine water - Value: 0.026 mg/l  
 Target: Freshwater sediments - Value: 1.25 mg/kg  
 Target: Marine water sediments - Value: 0.125 mg/kg  
 Target: Soil (agricultural) - Value: 0.24 mg/kg  
 Target: orally (secondary poisoning) - Value: 200 mg/kg - Notes:: Dietetico  
 Target: STP - Value: 650 mg/l

toluene - CAS: 108-88-3  
 Target: Fresh Water - Value: 0.68 mg/l  
 Target: Marine water - Value: 0.68 mg/l  
 Target: Soil (agricultural) - Value: 2.89 mg/kg  
 Target: Marine water sediments - Value: 16.39 mg/l  
 Target: Freshwater sediments - Value: 16.39 mg/l  
 Target: STP - Value: 13.61 mg/l

butanone - CAS: 78-93-3  
 Target: Marine water - Value: 55.8 mg/l  
 Target: Fresh Water - Value: 55.8 mg/l  
 Target: occasional emission - Value: 55.8 mg/l  
 Target: STP - Value: 709 mg/l

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

Target: Freshwater sediments - Value: 284.7 mg/kg dwt  
Target: Marine water sediments - Value: 284.7 mg/kg dwt  
Target: Soil (agricultural) - Value: 22.5 mg/kg  
Target: orally (secondary poisoning) - Value: 1000 mg/kg  
hexamethylene-di-isocyanate - CAS: 822-06-0  
Target: Marine water - Value: 0.00774 mg/l  
Target: Fresh Water - Value: 0.0774 mg/l  
Target: Freshwater sediments - Value: 0.01334 mg/kg - Notes:: Dry weight  
Target: Marine water sediments - Value: 0.001334 mg/kg - Notes:: Dry weight  
Target: Soil (agricultural) - Value: 0.0026 mg/kg - Notes:: Dry weight  
Target: Microorganisms in sewage treatments - Value: 8.42 mg/l

#### 8.2. Exposure controls

##### Eye protection:

Use eye protection devices. Example: closed safety visors, goggles with side protection. Do not wear contact lenses.

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Because of the synergetic effect of the substances contained in the formulation it is not possible to identify a unique material that can resist to their fusion. Multi - layer protective gloves can be suitable for mixes of substances. Pay attention to the data about grade of protection and of permeation rate furnished by the producer of the gloves about the substances listed on point 3 of this sheet.

##### Respiratory protection:

Use adequate protective respiratory equipment, e.g. A2 or A2P2 or A2P3.

##### Thermal Hazards:

None known

##### Environmental exposure controls:

None known

##### Appropriate engineering controls:

None

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance and colour:	liquid
Odour:	characteristic
Odour threshold:	N.A.
pH:	N.A.
Melting point / freezing point:	< 1°C
Initial boiling point and boiling range:	> 55°C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	< 23°C (< 73.4 °F)
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	0.9350 Kg/l a 20°C
Solubility in water:	N.A.
Solubility in oil:	N.A.
Partition coefficient (n-octanol/water):	N.A.



## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

Auto-ignition temperature: > 250°C  
Decomposition temperature: N.A.

Explosive properties: N.A.  
Oxidizing properties: N.A.

#### 9.2. Other information

Miscibility: N.A.  
Fat Solubility: N.A.  
Conductivity: N.A.  
Substance Groups relevant properties: N.A.

---

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Stable under normal conditions

#### 10.3. Possibility of hazardous reactions

No dangerous reaction is stored and used appropriately.

#### 10.4. Conditions to avoid

Avoid accumulating electrostatic charge.  
Vapours can form explosive mixtures with air.

#### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

#### 10.6. Hazardous decomposition products

vapours potentially dangerous to health may be released.

---

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

n-butyl acetate - CAS: 123-86-4

##### a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 21 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 10736 mg/kg - Notes: Method OECD linee guide 402

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

ethyl acetate - CAS: 141-78-6

##### a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit > 20000 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 5620 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 29.3 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rabbit = 4934 mg/kg body weight

##### b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit Negative

##### e) germ cell mutagenicity:

Test: Genotoxicity Negative

##### j) aspiration hazard:

Test: Respiratory Tract Corrosive - Route: Inhalation Positive

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 636 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 12267 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 25.7 mg/l - Duration: 4h

butanone - CAS: 78-93-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 2737 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 6480 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h

b) skin corrosion/irritation:

Test: Skin Corrosive - Species: Rabbit Negative - Notes: moderatamente irritante

hexamethylene-di-isocyanate - CAS: 822-06-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 746 mg/kg - Notes: Method: OECD TG 401

Test: LD50 - Route: Skin - Species: Rabbit > 7000 mg/kg - Notes: Method: OECD TG 402

Test: LC50 - Route: Inhalation - Species: Rat = 0.124 mg/l - Duration: 4h - Notes: Method: OECD TG 403 - Conc. del vapore saturo di 1,6-HDI a 25°C 0,095 mg/l

Test: NOAEL - Route: Inhalation - Species: Rat 0.035 mg/m<sup>3</sup> - Duration: 6h - Notes:

Method OECD linee guide 453

Test: LOAEL - Route: Inhalation - Species: Rat 0.175 mg/m<sup>3</sup> - Duration: 6h - Notes:

Method OECD linee guide 453

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 64 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia = 73 mg/l - Duration h: 24

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

ethyl acetate - CAS: 141-78-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 454.7 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 154 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3300 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae > 100 mg/l - Duration h: 72

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 12500 Ppm - Duration h: 72

Endpoint: EC50 - Species: Algae > 433 Ppm - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 1000 Ppm - Duration h: 504

butanone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 3220 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 520 mg/l - Duration h: 48

#### 12.2. Persistence and degradability

None known

N.A.

#### 12.3. Bioaccumulative potential

N.A.

#### 12.4. Mobility in soil

N.A.

#### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

#### 12.6. Other adverse effects

None known

---

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

---

## SECTION 14: Transport information

### 14.1. UN number

ADR-UN Number: 1263

IATA-Un number: 1263

IMDG-Un number: 1263

### 14.2. UN proper shipping name

ADR-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IATA-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

### 14.3. Transport hazard class(es)

ADR-Class: 3

ADR-Label: 3

ADR - Hazard identification number: 33

IATA-Class: 3

IATA-Label: 3

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

IMDG-Class:	3
14.4. Packing group	
ADR-Packing Group:	II
IATA-Packing group:	II
IMDG-Packing group:	II
14.5. Environmental hazards	
14.6. Special precautions for user	
ADR-Tunnel Restriction Code:	2 (D/E)
IATA-Passenger Aircraft:	353
IATA-Cargo Aircraft:	364
IMDG-Technical name:	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
IMDG-EMS:	F-E , <u>S-E</u>
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
No	

#### SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work.

1999/13/EC (VOC directive)

Directive 1999/13/CE

Total Volatile Organic Compounds (typical value): 76 %

Total Volatile Organic Carbon (typical value):

47.76 %

Total solids content: 23.6 - 24.4 %

15.2. Chemical safety assessment

No

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

---

#### SECTION 16: Other information

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H302 Harmful if swallowed.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Paragraphs modified from the previous revision:

SECTION 3: Composition/information on ingredients

SECTION 8: Exposure controls/personal protection

SECTION 11: Toxicological information

SECTION 12: Ecological information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eighth Edition - Van  
Nostrand Reinold

ACGIH - Threshold Limit Values - 2004 edition

RESTRICTED TO PROFESSIONAL USERS

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.



## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.
N.A.:	N.A.
N.D.:	

End of Safety Data Sheet

## Safety Data Sheet

### 385348 - Cth30 Polyurethane Hardner 451

Label model

# 385348

## Cth30 Polyurethane Hardner 451



Hazard pictograms:

Danger

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.

Precautionary statements:

- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground/bond container and receiving equipment.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P370+P378 In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders to extinguish.

Special Provisions:

- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.

Contains

- n-butyl acetate
- ethyl acetate
- Alifatic-aromatic polyisocyanate
- toluene
- hexamethylene-di-isocyanate: May produce an allergic reaction.

**Quantity:**

**Company:**