



## Safety Data Sheet

### 386541 - lpp2540nc-Lucido pol.pigm. nero

Safety Data Sheet dated 13/9/2017, version 14

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: lpp2540nc-Lucido pol.pigm. nero

Trade code: 386541

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Surface coating

---

1.3. Details of the supplier of the safety data sheet

Company:

Sirca S.p.A.

Address:

Viale Roma, 85  
35010 S.Dono di Massanzago (PD) - ITALY  
Tel. +39 0499322311

Competent person responsible for the safety data sheet:

safety@sirca.it

1.4. Emergency telephone number

National Poisons Information Service - Medical Center Chaim Shiba - Tel Ha' shomer - Phone

+972 - 3 - 5303030

Sirca S.p.A. +39 049 9322311 (08.00 - 17.00) From Monday to Friday

#### SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards known

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P370+P378 In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders to extinguish.

#### Special Provisions:

None

#### Contains

xylene [isomer mixture]

#### Special provisions according to Annex XVII of REACH and subsequent amendments:

None

#### 2.3. Other hazards

#### Other Hazards:

No other hazards known

---

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 25% - < 48% xylene [isomer mixture]

REACH No.: 01-2119488216-32-xxxx, Index number: 601-022-00-9, CAS: 1330-20-7, EC: 215-535-7

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.9/2 STOT RE 2 H373

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Dermal Acute Tox. 4 H312

⚠ 3.1/4/Inhal Acute Tox. 4 H332

>= 7% - < 9.9% n-butyl acetate

REACH No.: 01-2119485493-29-xxxx, Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.8/3 STOT SE 3 H336

EUH066

>= 3% - < 5% ethylbenzene

REACH No.: 01-2119489370-35-xxxx, Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

- ⚠ 2.6/2 Flam. Liq. 2 H225
- ⚠ 3.1/4/Inhal Acute Tox. 4 H332
- ⚠ 3.9/2 STOT RE 2 H373
- ⚠ 3.10/1 Asp. Tox. 1 H304

>= 2.5% - < 3% 2-methoxy-1-methylethyl acetate

REACH No.: 01-2119475791-29-xxxx, Index number: 607-195-00-7, CAS: 108-65-6, EC: 203-603-9

- ⚠ 2.6/3 Flam. Liq. 3 H226

>= 0.5% - < 1% 4-methylpentan-2-one; isobutyl methyl ketone

REACH No.: 01-2119473980-30-xxxx, Index number: 606-004-00-4, CAS: 108-10-1, EC: 203-550-1

- ⚠ 2.6/2 Flam. Liq. 2 H225
  - ⚠ 3.3/2 Eye Irrit. 2 H319
  - ⚠ 3.8/3 STOT SE 3 H335
  - ⚠ 3.1/4/Inhal Acute Tox. 4 H332
- EUH066

>= 0.1% - < 0.2% (2-Methoxymethylethoxy)propanol

REACH No.: 01-2119450011-60-xxxx, CAS: 34590-94-8, EC: 252-104-2

Substance with a Union workplace exposure limit.

---

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Induce vomiting only on doctor's advice

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

##### 4.2. Most important symptoms and effects, both acute and delayed

Contact a poisons centre

##### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

---

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

Suitable extinguishing media:

In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

- 5.2. Special hazards arising from the substance or mixture  
Combustion may liberate toxic or very toxic gases. Do not breathe fumes.  
Do not inhale explosion and combustion gases.  
Burning produces heavy smoke.
- 5.3. Advice for firefighters  
Use suitable breathing apparatus .  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures  
Wear personal protection equipment.  
Remove all sources of ignition.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
Provide adequate ventilation.  
Remove persons to safety.  
Use appropriate respiratory protection.  
See protective measures under point 7 and 8.
- 6.2. Environmental precautions  
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.  
Retain contaminated washing water and dispose it.  
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.  
Suitable material for taking up: absorbing material, organic, sand  
Eliminate all unguarded flames and possible sources of ignition. Do not smoke.
- 6.3. Methods and material for containment and cleaning up  
Collect the spilled product with no-sparking tools.  
  
Rapidly recover the product. To do so, wear a mask and protective clothing.  
Recover the product for re-use if possible, or for elimination. The product might, where appropriate, be absorbed by inert material.  
After the product has been recovered, rinse the area and materials involved with water.
- 6.4. Reference to other sections  
See also section 8 and 13

---

#### SECTION 7: Handling and storage

- 7.1. Precautions for safe handling  
Keep away from flame and sparks. Avoid accumulating electrostatic charge.  
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.  
Avoid contact with skin and eyes, inhalation of vapours and mists.  
Use localized ventilation system.  
Don't use empty container before they have been cleaned.  
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Do not smoke while working.

See also section 8 for recommended protective equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store at below 30 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

#### 7.3. Specific end use(s)

No further recommendations. Refer to point 1.2

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

xylene [isomer mixture] - CAS: 1330-20-7

(OEL (IT)) - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Behaviour:

Binding - Notes: pelle

EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

n-butyl acetate - CAS: 123-86-4

TWA (Italia) - TWA: 150 ppm - STEL: 200 ppm

ACGIH - TWA: 150 ppm - STEL: 200 ppm - Notes: Eye and URT irr

ethylbenzene - CAS: 100-41-4

(OEL (IT)) - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Behaviour:

Binding - Notes: pelle

EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

(OEL (IT)) - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Behaviour:

Binding - Notes: Pelle

EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

(OEL (IT)) - TWA(8h): 83 mg/m<sup>3</sup>, 20 ppm - STEL: 208 mg/m<sup>3</sup>, 50 ppm - Behaviour:

Binding

EU - TWA(8h): 83 mg/m<sup>3</sup>, 20 ppm - STEL: 208 mg/m<sup>3</sup>, 50 ppm

ACGIH - TWA(8h): 20 ppm - STEL: 75 ppm - Notes: A3, BEI - URT irr, dizziness, headache

(2-Methoxymethylethoxy)propanol - CAS: 34590-94-8

(OEL (IT)) - TWA(8h): 308 mg/m<sup>3</sup>, 50 ppm - Behaviour: Binding - Notes: pelle

EU - TWA(8h): 308 mg/m<sup>3</sup>, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: Skin - Eye and URT irr, CNS impair

#### DNEL Exposure Limit Values

xylene [isomer mixture] - CAS: 1330-20-7

Worker Industry: 180 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term,

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

- systemic effects
- Worker Industry: 77 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- Consumer: 108 mg/Kg-bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
- Consumer: 1872 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
- Consumer: 12.5 mg/Kg-bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
- n-butyl acetate - CAS: 123-86-4
  - Worker Professional: 600 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Worker Professional: 300 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
  - Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
  - Consumer: 300 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Consumer: 35.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects
  - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects
  - Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
  - Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
- ethylbenzene - CAS: 100-41-4
  - Worker Industry: 180 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Industry: 293 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Worker Industry: 77 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
  - Worker Professional: 153.5 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Professional: 275 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Consumer: 54.8 mg/kg/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Consumer: 1.67 mg/kg/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
- 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1
  - Worker Industry: 208 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)
  - Worker Industry: 208 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects
  - Worker Industry: 11.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated)

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

Worker Industry: 83 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term (repeated)

Worker Industry: 83 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 155.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)

Consumer: 155.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Consumer: 4.2 mg/kg - Exposure: Human Dermal - Frequency: Long Term (repeated)

Consumer: 14.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term (repeated)

Consumer: 4.2 mg/kg - Exposure: Human Oral - Frequency: Long Term (repeated)

(2-Methoxymethylethoxy)propanol - CAS: 34590-94-8

Worker Industry: 310 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 65 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 1.67 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 37.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 15 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

#### PNEC Exposure Limit Values

xylene [isomer mixture] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Fresh Water - Value: 0.327 mg/l

Target: occasional emission - Value: 0.327 mg/l

Target: Microorganisms in sewage treatments - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg - Notes:: dry

Target: Marine water sediments - Value: 12.46 mg/kg - Notes:: dry

Target: Freshwater sediments - Value: 12.46 mg/kg - Notes:: dry

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: Freshwater sediments - Value: 0.981 mg/kg

Target: Marine water sediments - Value: 0.0981 mg/kg

Target: Soil (agricultural) - Value: 0.0903 mg/kg

Target: STP - Value: 35.6 mg/l

ethylbenzene - CAS: 100-41-4

Target: Fresh Water - Value: 0.1 mg/l

Target: Marine water - Value: 0.01 mg/l

Target: Marine water sediments - Value: 13.7 mg/l

Target: Freshwater sediments - Value: 13.7 mg/l

Target: occasional emission - Value: 0.1 mg/l

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Fresh Water - Value: 0.635 mg/l

Target: Marine water - Value: 0.0635 mg/l

Target: Marine water sediments - Value: 0.329 mg/kg - Notes:: dry

Target: Freshwater sediments - Value: 3.29 mg/kg - Notes:: dry

Target: Soil (agricultural) - Value: 0.29 mg/kg - Notes:: dry

Target: STP - Value: 100 mg/l

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

Target: Fresh Water - Value: 0.6 mg/l

Target: Marine water - Value: 0.06 mg/l

Target: Freshwater sediments - Value: 8.27 mg/kg

Target: Marine water sediments - Value: 0.83 mg/kg

Target: Soil (agricultural) - Value: 1.3 mg/kg

#### 8.2. Exposure controls

##### Eye protection:

Use eye protection devices. Example: closed safety visors, goggles with side protection. Do not wear contact lenses.

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Because of the synergetic effect of the substances contained in the formulation it is not possible to identify a unique material that can resist to their fusion. Multi - layer protective gloves can be suitable for mixes of substances. Pay attention to the data about grade of protection and of permeation rate furnished by the producer of the gloves about the substances listed on point 3 of this sheet.

##### Respiratory protection:

Use adequate protective respiratory equipment, e.g. A2 or A2P2 or A2P3.

##### Thermal Hazards:

None known

##### Environmental exposure controls:

None known

##### Appropriate engineering controls:

None

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |                  |
|---|------------------|
| Appearance and colour:                        | liquid           |
| Odour:  | characteristic   |
| Odour threshold:                              | N.A.             |
| pH:   | N.A.             |
| Melting point / freezing point:               | < 1°C            |
| Initial boiling point and boiling range:      | > 55°C           |
| Solid/gas flammability:                       | N.A.             |
| Upper/lower flammability or explosive limits: | N.A.             |
| Vapour density:                               | N.A.             |
| Flash point:                                  | 23°C ≤ fp ≤ 60°C |
| Evaporation rate:                             | N.A.             |
| Vapour pressure:                              | N.A.             |
| Relative density:                             | 1 Kg/l a 20°C    |
| Solubility in water:                          | N.A.             |
| Solubility in oil:                            | N.A.             |
| Partition coefficient (n-octanol/water):      | N.A.             |
| Auto-ignition temperature:                    | > 250°C          |
| Decomposition temperature:                    | N.A.             |
| Explosive properties:                         | N.A.             |
| Oxidizing properties:                         | N.A.             |



## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

#### 9.2. Other information

|                                      |      |
|--------------------------------------|------|
| Miscibility:                         | N.A. |
| Fat Solubility:                      | N.A. |
| Conductivity:                        | N.A. |
| Substance Groups relevant properties | N.A. |

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

No dangerous reaction is stored and used appropriately.

### 10.4. Conditions to avoid

Avoid accumulating electrostatic charge.  
Vapours can form explosive mixtures with air.

### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

### 10.6. Hazardous decomposition products

vapours potentially dangerous to health may be released.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

xylene [isomer mixture] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Inhalation - Species: Rat = 27 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 12126 mg/kg

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 21 mg/l - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 10736 mg/kg - Notes: Method OECD linee guide 402

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit = 15400 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 4000 Ppm - Duration: 4h

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin - Species: Cavia porcellus Negative

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 8532 mg/kg

Test: LC50 - Route: Skin - Species: Rat > 5000 mg/kg

Test: LC50 - Route: Inhalation Mist - Species: Rat > 23.8 mg/l - Duration: 6h

b) skin corrosion/irritation:

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

- Test: Skin Irritant - Route: Skin - Species: Rabbit Negative  
4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1
- a) acute toxicity:  
Test: LC50 - Route: Inhalation - Species: Rat = 23.29 g/m<sup>3</sup>  
Test: LD50 - Route: Oral - Species: Rat = 2080 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat = 8.2 mg/l - Duration: 4h  
Test: LD50 - Route: Skin - Species: Rabbit = 2000 mg/kg
- (2-Methoxymethylethoxy)propanol - CAS: 34590-94-8
- a) acute toxicity:  
Test: LC50 - Route: Inhalation - Species: Rat > 275 Ppm - Duration: 7h  
Test: LC50 - Route: Oral - Species: Rat > 5000 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 19020 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

xylene [isomer mixture] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 3.2 mg/l - Duration h: 96

Endpoint: LC50 - Species: Algae = 2.6 mg/l - Duration h: 73

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 64 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia = 73 mg/l - Duration h: 24

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 42.3 mg/l - Duration h: 96

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: Method OECD linee guide 203

Endpoint: EC50 - Species: Daphnia > 500 mg/l - Duration h: 48 - Notes: Method Direttiva 67/548CEE allegato V,C.2

Endpoint: ErC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: Method OECD TG 209

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 100 mg/l

(2-Methoxymethylethoxy)propanol - CAS: 34590-94-8

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 969 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish > 10000 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia = 1919 mg/l - Duration h: 48

12.2. Persistence and degradability

None known

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None known

#### SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

#### SECTION 14: Transport information

14.1. UN number

ADR-UN Number: 1263

IATA-Un number: 1263

IMDG-Un number: 1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IATA-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

ADR-Class: 3

ADR-Label: 3

ADR - Hazard identification number: 33

IATA-Class: 3

IATA-Label: 3

IMDG-Class: 3

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

- 14.4. Packing group  
 ADR-Packing Group: II  
 IATA-Packing group: II  
 IMDG-Packing group: II
- 14.5. Environmental hazards
- 14.6. Special precautions for user  
 ADR-Tunnel Restriction Code: 2 (D/E)  
 IATA-Passenger Aircraft: 353  
 IATA-Cargo Aircraft: 364  
 IMDG-Technical name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)  
 IMDG-EMS: F-E , S-E
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
 No

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
 Dir. 98/24/EC (Risks related to chemical agents at work)  
 Dir. 2000/39/EC (Occupational exposure limit values)  
 Regulation (EC) n. 1907/2006 (REACH)  
 Regulation (EC) n. 1272/2008 (CLP)  
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
 Regulation (EU) 2015/830  
 Regulation (EU) n. 286/2011 (ATP 2 CLP)  
 Regulation (EU) n. 618/2012 (ATP 3 CLP)  
 Regulation (EU) n. 487/2013 (ATP 4 CLP)  
 Regulation (EU) n. 944/2013 (ATP 5 CLP)  
 Regulation (EU) n. 605/2014 (ATP 6 CLP)  
 Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
 Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:  
 None
- Where applicable, refer to the following regulatory provisions :  
 Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.  
 Regulation (EC) nr 648/2004 (detergents).  
 Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work.
- 1999/13/EC (VOC directive)  
 Directive 1999/13/CE
- |   |               |         |
|---|---------------|---------|
| Total Volatile Organic Compounds (typical value): | 44 %          |         |
| Total Volatile Organic Carbon (typical value):    |               | 35.49 % |
| Total solids content:                             | 53.9 - 56.1 % |         |
- 15.2. Chemical safety assessment  
 No

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

#### SECTION 16: Other information

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H315 Causes skin irritation.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour.

Paragraphs modified from the previous revision:

SECTION 8: Exposure controls/personal protection

SECTION 11: Toxicological information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eighth Edition - Van  
Nostrand Reinold

ACGIH - Threshold Limit Values - 2004 edition

RESTRICTED TO PROFESSIONAL USERS

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

|             |  |
|-------------|--|
| ADR:        | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
| CAS:        | Chemical Abstracts Service (division of the American Chemical Society).              |
| CLP:        | Classification, Labeling, Packaging.   |
| DNEL:       | Derived No Effect Level.   |
| EINECS:     | European Inventory of Existing Commercial Chemical Substances.                       |
| GefStoffVO: | Ordinance on Hazardous Substances, Germany.  |
| GHS:        | Globally Harmonized System of Classification and Labeling of Chemicals.              |
| IATA:       | International Air Transport Association.   |
| IATA-DGR:   | Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  |
| ICAO:       | International Civil Aviation Organization.   |
| ICAO-TI:    | Technical Instructions by the "International Civil Aviation Organization" (ICAO).    |
| IMDG:       | International Maritime Code for Dangerous Goods.                                     |
| INCI:       | International Nomenclature of Cosmetic Ingredients.                                  |
| KSt:        | Explosion coefficient.   |
| LC50:       | Lethal concentration, for 50 percent of test population.                             |



## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

|         |   |
|---------|---|
| LD50:   | Lethal dose, for 50 percent of test population.                                   |
| LTE:    | Long-term exposure.   |
| PNEC:   | Predicted No Effect Concentration.  |
| RID:    | Regulation Concerning the International Transport of Dangerous Goods by Rail.     |
| STE:    | Short-term exposure.  |
| STEL:   | Short Term Exposure limit.  |
| STOT:   | Specific Target Organ Toxicity.   |
| TLV:    | Threshold Limiting Value.   |
| TWATLV: | Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard). |
| WGK:    | German Water Hazard Class.  |
| N.A.:   | N.A.  |
| N.D.:   |   |

End of Safety Data Sheet

## Safety Data Sheet

### 386541 - Ipp2540nc-Lucido pol.pigm. nero

Label model

---

# 386541

## Ipp2540nc-Lucido pol.pigm. nero



Hazard pictograms:

Warning

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P370+P378 In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders to extinguish.

Special Provisions:

None

Contains

xylene [isomer mixture]

---

**Quantity:**

**Company:**

---