

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** CONDUCTING PAINT ONE COMPONENT FOR PLASTIC
- **Article number:** 399-993
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 No further relevant information available.
- **Application of the substance / the mixture** PAINT
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** TAMBOUR LTD.
- **Further information obtainable from:** Health & Safety
- **1.4 Emergency telephone number:** *6477

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger

- **Hazard-determining components of labelling:**

n-butyl acetate

- **Hazard statements**
- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

Trade name: CONDUCTING PAINT ONE COMPONENT FOR PLASTIC

(Contd. of page 1)

P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	25-50%
CAS: 78-93-3 EINECS: 201-159-0	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-10%
CAS: 123-42-2 EINECS: 204-626-7	4-hydroxy-4-methylpentan-2-one Flam. Liq. 3, H226; Eye Irrit. 2, H319	2.5-10%
CAS: 872-50-4 EINECS: 212-828-1	N-methyl-2-pyrrolidone Repr. 1B, H360D; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<1%

· SVHC

872-50-4 N-methyl-2-pyrrolidone

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· 5.3 Advice for firefighters

· **Protective equipment:** No special measures required.

GB

(Contd. on page 3)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

Trade name: **CONDUCTING PAINT ONE COMPONENT FOR PLASTIC**

(Contd. of page 2)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL (Great Britain)	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
TLV (Israel)	Long-term value: 150 ppm

78-93-3 butanone

WEL (Great Britain)	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
TLV (Israel)	Long-term value: 200 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
TLV (Israel)	Long-term value: 50 ppm

(Contd. on page 4)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

Trade name: CONDUCTING PAINT ONE COMPONENT FOR PLASTIC

(Contd. of page 3)

123-42-2 4-hydroxy-4-methylpentan-2-one

WEL (Great Britain) Short-term value: 362 mg/m³, 75 ppm
 Long-term value: 241 mg/m³, 50 ppm

872-50-4 N-methyl-2-pyrrolidone

WEL (Great Britain) Short-term value: 80 mg/m³, 20 ppm
 Long-term value: 40 mg/m³, 10 ppm
 Sk

· **Ingredients with biological limit values:**

78-93-3 butanone

BMGV (Great Britain) 70 µmol/L
 Medium: urine
 Sampling time: post shift
 Parameter: butan-2-one

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Colour:

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

(Contd. on page 5)

GB

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

Trade name: **CONDUCTING PAINT ONE COMPONENT FOR PLASTIC**

(Contd. of page 4)

· pH-value:	Not determined.
· Change in condition Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	79-80.5 °C
· Flash point:	-4 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower:	1.4 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	105 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content: Organic solvents:	61.7 %
VOC Content	61.73 % 617.3 g/l / 5.15 lb/gal
Solids content:	30.4 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

Trade name: CONDUCTING PAINT ONE COMPONENT FOR PLASTIC

(Contd. of page 5)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number** .
- **ADR, IMDG, IATA** UN1993
- **14.2 UN proper shipping name** .
- **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50°C not more than 110 kPa) (ETHYL METHYL KETONE (METHYL ETHYL KETONE), BUTYL ACETATES)
- **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (ETHYL METHYL KETONE (METHYL ETHYL KETONE), BUTYL ACETATES)

(Contd. on page 7)

GB

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

Trade name: **CONDUCTING PAINT ONE COMPONENT FOR PLASTIC**

(Contd. of page 6)

· 14.3 Transport hazard class(es)

.

· ADR, IMDG, IATA



· Class

3 Flammable liquids.

· Label

3

· 14.4 Packing group

.

· ADR, IMDG, IATA

II

· 14.5 Environmental hazards:

· Marine pollutant:

No

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Danger code (Kemler):

33

· EMS Number:

F-E,S-E

· Stowage Category

B

· 14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· Tunnel restriction code

D/E

· IMDG

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (VAPOUR
 PRESSURE AT 50°C NOT MORE THAN 110 KPA)
 (ETHYL METHYL KETONE (METHYL ETHYL KETONE),
 BUTYL ACETATES), 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms GHS02, GHS07

· Signal word Danger

· Hazard-determining components of labelling:

n-butyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 8)

Safety data sheet
Conform to Regulation EC No. 1907/2006 amended by Regulation
(EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

Trade name: CONDUCTING PAINT ONE COMPONENT FOR PLASTIC

(Contd. of page 7)

· **Precautionary statements**

- P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
- P241 *Use explosion-proof electrical/ventilating/lighting equipment.*
- P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
- P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P405 *Store locked up.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c **FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 30

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
III	16.8
NK	61.7

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

872-50-4	N-methyl-2-pyrrolidone
----------	------------------------

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H315 *Causes skin irritation.*
- H319 *Causes serious eye irritation.*
- H335 *May cause respiratory irritation.*
- H336 *May cause drowsiness or dizziness.*
- H360D *May damage the unborn child.*

- **Department issuing SDS:** Tambour Ltd.- Health & Safety Department.

· **Contact:**

Moti Adler
 Phone: +972(4)985-3795
 e-mail: motiA@tambour.co.il

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

Safety data sheet
Conform to Regulation EC No. 1907/2006 amended by Regulation
(EU) No. 453/2010

Printing date 19.02.2018

Version number 1

Revision: 19.02.2018

Trade name: CONDUCTING PAINT ONE COMPONENT FOR PLASTIC

(Contd. of page 8)

VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**

GB