

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** SYNTHETIC MATTE YELLOW SAND PAINT
- **Article number:** 441-006
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 No further relevant information available.
- **Application of the substance / the mixture** PAINT
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 TAMBOUR LTD.
 Meir Ariel st. 6
 Netanya 42504, Israel
 Phone: +972-9-8925555
 www.tambour.co.il
- **Further information obtainable from:**
 Phone: +972(4)985-3795
 e-mail: motiA@tambour.co.il
- **1.4 Emergency telephone number:** Tambour call center: +972-74-7545688 or *6477

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.
 STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

Safety data sheet
Conform to Regulation EC No. 1907/2006 amended by Regulation
(EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 1)

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS07, GHS08, GHS09
- **Signal word** Warning
- **Hazard-determining components of labelling:**
 toluene
 Naphtha (petroleum), hydrodesulfurized heavy
- **Hazard statements**
 H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to the central nervous system through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
 Contains 2-butanone oxime. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 108-88-3 EINECS: 203-625-9	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene (mix) Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 7779-90-0 EINECS: 231-944-3	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-10%
CAS: 64742-95-6 EC number: 918-668-5	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-10%
CAS: 1314-13-2 EINECS: 215-222-5	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-2.5%

(Contd. on page 3)

GB

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 2)

CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226; Asp. Tox. 1, H304	1-2.5%
CAS: 12001-26-2	Mica substance with a Community workplace exposure limit	1-2.5%
CAS: 96-29-7 EINECS: 202-496-6	2-butanone oxime Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317	<1%
CAS: 15956-58-8 EINECS: 240-085-3	2-ethylhexanoic acid, manganese salt Repr. 2, H361fd; STOT RE 2, H373; Aquatic Chronic 2, H411; Eye Irrit. 2, H319	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** No special requirements.· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:** Keep container tightly sealed.· **7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection**· **Additional information about design of technical facilities:** No further data; see item 7.· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****108-88-3 toluene**

WEL (Great Britain)	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk
TLV (Israel)	Long-term value: 50 ppm

1330-20-7 xylene (mix)

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
TLV (Israel)	Short-term value: 150 ppm Long-term value: 100 ppm

12001-26-2 Mica

WEL (Great Britain)	Long-term value: 10* 0.8** mg/m ³ *total inhalable **respirable
---------------------	---

· **Ingredients with biological limit values:****108-88-3 toluene**

TLV-TWA (Israel)	50
TLV_TWA (Israel)	50

1330-20-7 xylene (mix)

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
----------------------	--

· **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 5)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 4)

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.
- **Respiratory protection:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Fluid
Colour:	According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	137 °C
- **Flash point:** 30 °C
- **Flammability (solid, gas):** Not applicable.

(Contd. on page 6)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 5)

· Ignition temperature:	265 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	6.5 Vol %
· Vapour pressure at 20 °C:	6.6 hPa
· Density at 20 °C:	1.27 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	38.4 %
VOC Content	38.39 % 487.6 g/l / 4.07 lb/gal
Solids content:	65.6 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rab)
Inhalative	LC50/4 h	5,320 mg/l (mus)

(Contd. on page 7)

GB

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 6)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**
Suspected of damaging the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to the central nervous system through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263

(Contd. on page 8)

GB

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 7)

· **14.2 UN proper shipping name**
 · **ADR**
 · **IMDG**
 · **IATA**

1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (Naphtha (petroleum), hydrodesulfurized heavy, trizinc bis(orthophosphate)), MARINE POLLUTANT PAINT

· **14.3 Transport hazard class(es)**· **ADR, IMDG**

· **Class**
 · **Label**

3 Flammable liquids.
3

· **IATA**

· **Class**
 · **Label**

3 Flammable liquids.
3

· **14.4 Packing group**· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: trizinc bis(orthophosphate)

· **Marine pollutant:**

Yes

Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Danger code (Kemler):**

30

· **EMS Number:**

F-E, S-E

· **Stowage Category**

A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category**

3

· **Tunnel restriction code**

D/E

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

Safety data sheet
 Conform to Regulation EC No. 1907/2006 amended by Regulation
 (EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 8)

· UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms** GHS02, GHS07, GHS08, GHS09

· **Signal word** Warning

· **Hazard-determining components of labelling:**

toluene

Naphtha (petroleum), hydrodesulfurized heavy

· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 40, 48

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
I	0.2
NK	38.4

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

(Contd. on page 10)

Safety data sheet
Conform to Regulation EC No. 1907/2006 amended by Regulation
(EU) No. 453/2010

Printing date 03.03.2019

Version number 1

Revision: 03.03.2019

Trade name: SYNTHETIC MATTE YELLOW SAND PAINT

(Contd. of page 9)

- H226 *Flammable liquid and vapour.*
H304 *May be fatal if swallowed and enters airways.*
H312 *Harmful in contact with skin.*
H315 *Causes skin irritation.*
H317 *May cause an allergic skin reaction.*
H318 *Causes serious eye damage.*
H319 *Causes serious eye irritation.*
H332 *Harmful if inhaled.*
H335 *May cause respiratory irritation.*
H336 *May cause drowsiness or dizziness.*
H351 *Suspected of causing cancer.*
H361d *Suspected of damaging the unborn child.*
H361fd *Suspected of damaging fertility. Suspected of damaging the unborn child.*
H372 *Causes damage to the central nervous system through prolonged or repeated exposure.*
H373 *May cause damage to the central nervous system through prolonged or repeated exposure.*
H400 *Very toxic to aquatic life.*
H410 *Very toxic to aquatic life with long lasting effects.*
H411 *Toxic to aquatic life with long lasting effects.*

· **Department issuing SDS:** Tambour Ltd.- Health & Safety Department.

· **Contact:**

Moti Adler

Phone: +972(4)985-3795

e-mail: motiA@tambour.co.il

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**