





Page 1/9

Safety data sheet Conform to Regulation EC No. 1907/2006 amended by Regulation (EU) No. 453/2010

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: ROAD MARKING PAINT BLUE
- · Article number: 448-047/6
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: TAMBOUR LTD.
- · Further information obtainable from: Health & Safety
- · 1.4 Emergency telephone number: *6477

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d-H362 Suspected of damaging the unborn child. May cause harm to breast-fed

children

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07, GHS08
- · Signal word Danger
- · Hazard-determining components of labelling:

toluene

C14-17 Chlorinated parffin

· Hazard statements

H225 Highly flammable liquid and vapour.

(Contd. on page 2)

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

Trade name: ROAD MARKING PAINT BLUE

(Contd. of page 1)

H315 Causes skin irritation.

H361d-H362 Suspected of damaging the unborn child. May cause harm to breast-fed children.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dusts or mists.

P263 Avoid contact during pregnancy/while nursing.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 108-88-3	toluene	25-50%
EINECS: 203-625-9	Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 1330-20-7	xylene (mix)	2.5-10%
EINECS: 215-535-7	Flam. Liq. 3, H226; • Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit 2, H315	
CAS: 78-93-3	butanone	2.5-10%
EINECS: 201-159-0	🚸 Flam. Liq. 2, H225; 💠 Eye Irrit. 2, H319; STOT SE 3, H336	
	C14-17 Chlorinated parffin	1-2.5%
EINECS: 287-477-0	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

Trade name: ROAD MARKING PAINT BLUE

(Contd. of page 2)

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
108-88-3 toluene	
WEL (Great Britain)	Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk
TLV (Israel)	Long-term value: 50 ppm
1330-20-7 xylene (m	ix)
WEL (Great Britain)	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
	(Contd on m

(Contd. on page 4)

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

Trade name: ROAD MARKING PAINT BLUE

	(Contd. of page
TLV (Israel)	Short-term value: 150 ppm
	Long-term value: 100 ppm
78-93-3 butanone	
WEL (Great Britain)	Short-term value: 899 mg/m³, 300 ppm
	Long-term value: 600 mg/m³, 200 ppm
	Sk, BMGV
TLV (Israel)	Long-term value: 200 ppm
Ingredients with biole	ogical limit values:
108-88-3 toluene	
TLV-TWA (Israel)	50
TLV_TWA (Israel)	50
1330-20-7 xylene (mi	
BMGV (Great Britain) 650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
78-93-3 butanone	
BMGV (Great Britain,) 70 μmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material


The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

Trade name: ROAD MARKING PAINT BLUE

· Eye protection:



(Contd. of page 4)

0.17.0	, , , , , , , , , , , , , , , , , , ,
9.1 Information on basic physical and c General Information	hemical properties
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 110 °C
Flash point:	4 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	535 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive a vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	29 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	34.2 %
Water:	0.1 %
VOC Content	34.24 %
	342.7 g/l / 2.86 lb/gl

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

Trade name: ROAD MARKING PAINT BLUE

(Contd. of page 5)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
		12,124 mg/kg (rab)
Inhalative	LC50/4 h	5,320 mg/l (mus)

- Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging the unborn child. May cause harm to breast-fed children.

· STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 7)

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

Trade name: ROAD MARKING PAINT BLUE

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- $\cdot \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	mon
14.1 UN-Number ADR, IMDG, IATA	UNI 263
14.2 UN proper shipping name ADR	1263 PAINT (vapour pressure at 50°C not more than 1 kPa)
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33 F F G F
EMS Number: Stowage Category	F-E, <u>S-E</u> B
<u> </u>	
14.7 Transport in bulk according to Ani Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E

GB

Safety data sheet

Conform to Regulation EC No. 1907/2006 amended by Regulation (EU) No. 453/2010

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

Trade name: ROAD MARKING PAINT BLUE

(Contd. of page 7)

	(Conta. of page 7)
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
• •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07, GHS08
- · Signal word Danger
- · Hazard-determining components of labelling:

toluene

C14-17 Chlorinated parffin

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H361d-H362 Suspected of damaging the unborn child. May cause harm to breast-fed children.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dusts or mists.

P263 Avoid contact during pregnancy/while nursing.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	34.2

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

Printing date 27.02.2018 Version number 1 Revision: 27.02.2018

Trade name: ROAD MARKING PAINT BLUE

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H362 May cause harm to breast-fed children.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Tambour Ltd.- Health & Safety Department.

· Contact:

Moti Adler

Phone: +972(4)985-3795 e-mail: motiA@tambour.co.il

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

ICSO, Lethal concentration 50 percent

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Lact.: Reproductive toxicity – effects on or via lactation

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.